

LMR®-195 FLEXIBLE LOW LOSS CABLE ASSEMBLIES

Times LMR cable assemblies are high performance broadband, flexible, low-loss RF coaxial cables that can be used virtually anywhere, either indoors or outdoors. As a completely Times manufactured solution, performance and reliability are assured.



- Excellent RF Shielding, better than 90 dB
- UV and weather resistant
- Flexible and easy to use

Mechanical Properties


	Units	
Diameter	in (mm)	0.195 (4.95)
Weight	lb/ft (kg/m)	0.021 (0.03)
Minimum Bend Radius	in(mm)	0.5 (12.7)
Operating Temperature	°F (°C)	-40° to 185°(-40 to 85)
Tensile Strength	lb (kg)	40 (18.2)
Bending Moment	ft lb (N-m)	0.2 (0.27)
Flat Plate Crush	lb/in (kg/mm)	15 (0.27)
Storage Temp	°F (°C)	-94 to 185 (-70 to 85)

Electrical Properties

Units	
Ω	50 +/- 2
GHz	8.0
pF/ft (pF/m)	25.4 (83.3)
	80%
ns/ft (ns/m)	1.27 (4.17)
	>90dB minimum
Volts DC	1000
Volts RMS	3000
dB/ft	dB/m
0.11	(0.36)
0.19	(0.62)
0.3	(0.98)
	Ω GHz pF/ft (pF/m) ns/ft (ns/m) Volts DC Volts RMS dB/ft 0.11 0.19

KEY APPLICATIONS

- Antenna feeder runs
- Inter/intra cabinet jumpers
- Internal component equipment wiring
- GPS system wiring



Inner Conductor

Dielectric

3 Outer Conductor

4 Overall Braid

5 Jacket

Solid BC

Foam PE

Aluminum Tape

Tinned Copper

PΕ

LMR®-195 FLEXIBLE LOW LOSS CABLE ASSEMBLIES

Ordering Guide

LMR195- NMNM-3.0 F

Interface NM N Male SM SMA Male QM QMA Male TM TNC Male BM BNC Male Length

Units of Measure F Feet M Meters







WORLD HEADQUARTERS
358 Hall Avenue, Wallingford, CT 06492
1-800-867-2629

