

MaxGain® 200

High Performance Microwave Cable Assemblies

MaxGain® Assemblies are high-performance, ultra-low-loss microwave coaxial cables. Built with our unique spiral outer conductor technology, this light-weight cable is a reliable, high frequency interconnect solution.

Features

- Optimized for lowest attenuation at 30 GHz
- Ultra stable insertion loss, phase and VSWR with flexing
- Flexible, low minimum bend radius
- Superior shielding effectiveness (>90 dB)

Specifications

 Impedance
50 Ohms

 Op Temp
-67 to +302°F
-55 to +150°C

Units

Diameter	in (mm)	0.197 (5.00)
Weight	lb/ft (kg/m)	0.037 (0.055)
Minimum Bend Radius	in (mm)	1.0 (25.4)
Maximum Frequency	GHz	30
Velocity of Propagation	%	80
Capacitance	pF/ft (pF/m)	25.40 (83.3)
Delay	ns/ft (ns/m)	1.27 (4.17)
Shielding	dB	>90

Attenuation

	dB/ft	dB/m
18.0 GHz	0.356	1.17
28.5 GHz	0.457	2.61


Calculation

$$IL = (K1 \times \sqrt{f} + K2 \times f) \times \text{Cable Length} + \text{Connector 1 Loss} + \text{Connector 2 Loss}$$

Cable Insertion Loss
f = Frequency (MHz)

Use **K** values with
matching length unit

K values	dB/ft	dB/m
K1	0.0024610	0.0080740
K2	0.0000013	0.0000043



MaxGain® 200

High Performance Microwave Cable Assemblies



Ordering Guide

Available for cable assembly only

MG200 **- CODE** **CODE -** **XX.X** **M**

- Connector A Connector B - Length Units of measure
M - Meters
F - Feet

Connector Code	Description
NM	N Male
NF	N Female
TM	TNC Male
TF	TNC Female
SM	SMA Male
SF	SMA Female



Global manufacturing
capability: US, and Asia.



Heritage—in the air and on the ground,
thousands of assemblies built over decades.



Assembled and tested assemblies
provide assured performance.

Rev.5: 09/2024

Times Microwave Systems
358 Hall Avenue, Wallingford, CT 06492, USA
T 800. 867.2629
www.timesmicrowave.com