

XtendedFlex® 045



XtendedFlex® 045 is a micro-coaxial cable offering high flexibility and low shape memory. With its class-leading low attenuation, XF-045 maximizes power transfer efficiency in electrosurgical devices and signal integrity in industrial connectivity applications. The small diameter of XF-045 makes it an ideal coaxial component in high-density interconnects.

The XtendedFlex family of cables have been designed and tested to support high flex and continuous flex applications.

Features

- Ultra-flexible
- High Power Transfer Efficiency
- Lightweight
- Exceptional Flex Life

Specifications

Impedance
50 Ohms
 Op Temp
-67 to +302°F
-55 to +150°C

Units

Diameter	in (mm)	0.045 (1.14)
Weight	g/m	3.3
Minimum Bend Radius	in (mm)	0.20 (5.08)
Maximum Frequency	GHz	18
Velocity of Propagation	%	80
Capacitance	pF/ft (pF/m)	25.4 (83.3)
Time Delay	ns/ft (ns/m)	1.27 (4.17)
Shielding Effectiveness	dB	-60

Calculation

$$IL = (K1 \times \sqrt{f}) + K2 \times f \times \text{Cable Length}$$

Cable Insertion Loss
f = Frequency (MHz)

Use K values with
matching length unit

K Values **dB/100ft** **dB/100m**

K1	1.08320	3.55398
K2	0.000001	0.000005

CENTER CONDUCTOR

Silver Plated Copper

DIELECTRIC

PTFE Tape

OUTER CONDUCTOR

Silver Plated
Copper Flat Braid

JACKET

PFA

XtendedFlex® 045



Cable Assembly Ordering Guide

XF045

Cable Code

- Code

Connector A

Code -

Connector B

XX.X

Length

XX

Units of measure: I = Inches, CM = Centimeters

Code	Part Number	Stock Code	Description
MCXM	3190-7039	3190-7039	MCX, male, straight



Global manufacturing capability:
US, Asia, and India.



Assembled and tested assemblies
provide assured performance.

Rev. 5: 4/2026

Times Microwave Systems
358 Hall Avenue, Wallingford, CT 06492, USA
800.867.2629
www.timesmicrowave.com

XtendedFlex® is a registered trademark of Times Microwave Systems. All rights reserved.